







Air Tubular Trimmer

PPI-60-0713-1001x-000


PART SPECIFICATIONS

Tuning Torque	0.9 – 5.0 in. oz.	Rotational Life	≥ 75 cycles, IEC 418
Stop Torque	max 11.1 in. oz.	Vibration	60g / 10 – 2000Hz
Mounting Torque	---	Shock	1500g / 0.5 ms
Adjustment Accuracy	≤1 x 10 ⁻³ of adjusted value	Operating Temperature	-65°C...+125°C
Contact Resistance	< 0.001Ω	Dielectric	Air Tubular

Part Number	Cmin (pF)	Cmax (pF)	Test Voltage (VDC)	Q Factor @200 MHz	R _{insul.} (MΩ)	TC (ppm/°C)	Dim A (mm)	Dim B (mm)	Weight (g)
PPI-60-0713-10011-000	1.2	11.0	250	>5000	>10 ⁶	65 ± 30	4.1	---	2.3
PPI-60-0713-10016-000	1.2	16.0	250	>5000	>10 ⁶	65 ± 30	4.1	---	2.3



Optional Hardware



Seal Cap $\frac{+0.5}{+0.02}$
(Dim A): $\frac{+0.5}{+0.02}$

Dimensions are in $\frac{\text{mm}}{\text{inches}}$