




Air Tubular Trimmer

PPI-60-0728-150xx-000


PART SPECIFICATIONS

Part Number	Cmin (pF)	Cmax (pF)	Test Voltage (VDC)	Q Factor @200 MHz	R _{insul.} (MΩ)	TC (ppm/°C)	Dim A (mm)	Dim B (mm)	Weight (g)
PPI-60-0728-15010-000	0.8	10.0	500	>5000	>10 ⁶	0 ± 15	4.0	---	2.1
PPI-60-0728-15014-000	1.0	14.0	300	>5000	>10 ⁶	0 ± 15	4.0	---	2.1
PPI-60-0728-15016-000	1.2	16.0	300	>5000	>10 ⁶	0 ± 15	4.0	---	2.1

Tuning Torque	0.9 – 5.0 in. oz.	Rotational Life	≥ 75 cycles, IEC 418
Stop Torque	max 11.1 in. oz.	Vibration	60g / 10 – 2000Hz
Mounting Torque	----	Shock	1500g / 0.5 ms
Adjustment Accuracy	≤1 x 10 ⁻³ of adjusted value	Operating Temperature	-65°C...+125°C
Contact Resistance	< 0.001Ω	Dielectric	Air



Optional Hardware



Dimensions are in $\frac{\text{mm}}{\text{inches}}$