



PART SPECIFICATIONS

TUNING TORQUE	0.9 - 5.0 in.oz.
ROTATIONAL LIFE	≥ 75 cycles, IEC 418
STOP TORQUE	max 11.1 in.oz
VIBRATION	60 g / 10-2000Hz
MOUNTING TORQUE	----
SHOCK	1500g / 0.5ms
ADJUSTMENT ACCURACY	≤ 1 x 10 ³ of adjusted value
OPERATING TEMPERATURE	-65°C....+125°C
CONTACT RESISTANCE	< 0.001Ω
DIELECTRIC	Air

Part Number	Cmin (pF)	Cmax (pF)	Test Voltage (VDC)	Q-Factor (@200MHz)	IR (MΩ)	TC (ppm/°C)	Dim. A (mm)	Dim. B (mm)	Weight (g)	Optional Hardware	Figure
PPI-60-0753-15014-000	1	14.0	300	> 5000	>10 ⁶	0 ± 15	4	---	2.2	---	---
PPI-60-0753-15014-030	1	14.0	300	> 5000	>10 ⁶	0 ± 15	4	---	2.2	with Seal Cap Unmounted	A
PPI-60-0753-15014-019	1	14.0	300	> 5000	>10 ⁶	0 ± 15	4	---	2.2	with Slotted Seal Cap Unmounted	B



Optional Hardware

Figure A

Seal Cap Unmounted





Figure B

Slotted Seal Cap Unmounted



Dimensions are in $\frac{\text{mm}}{\text{inches}}$